ence Jalian

HMIS®

Material Safety Data Sheet	HMIS®				
May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be	HEALTH	1	REAC	TIVITY	0
consulted for specific requirements.	FLAMMABILITY		O PERSONAL PROTECTION		None
<b>IDENTITY</b> (As Used on Label and List) DRY BEA-307,308,309,317,320,363	REEZE	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.			
Section I					
Manufacturer's Name		Emergency Tele	Pohone Number		
Dymon, Inc.		800-255-4564			
Address (Number, Street, City, State, and ZIP Code)		Telephone Number for Information			
3401 Kansas Ave.  Kansas City, KS 66106		800-255-4564 Date Prepared			
		June 1, 1990			
		Signature of Pre Regulato			
Section II — Hazardous Ingredients/Ident	tity Information				
Hazardous Components (Specific Chemical Identity; C	ommon Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	96 (aptions
1,1,1 Trichloroethane		350ppm	350ppm	STEL 450pp	<b>% (optiona</b> ○m 5-20
(CAS No. 71-55	-6)				•
Isobutane (CAS No. 75-28-		800ppm	800ppm		
Propane (CAS No. 74-98-	-6)	1000ppm	Asphyxiant	-	
Any substance listed as hazardo and Pennsylvahia are described  Section III — Physical/Chemical Characte	above ii ki	nown present	alifornia, Mas in regulated G.TGreat	concentration	New Jerse
Boiling Point		Specific Gravity (H <sub>2</sub> O = 1)			
Concentrate-initial Vapor Pressure (mm Hg.)	165°F	Concentr	ate		1.25
at 70°F	60 75	Melting Point			
Vapor Density (AIR = 1)	60 psi	5			N.D.
, , , , , , , , , , , , , , , , , , ,	G.T.1	Evaporation Rate (Butyl Acetate =			N.D.
Solubility in Water		1 ()	'/		
1%					
Appearance and Odor					
Clear colorless liquid, foo	g from aer	osol, cha	racteristic	fresh scer	nts.
Section IV — Fire and Explosion Hazard					
Flash Point (Method Used)		Flammable Limits		Tier	F1
None to boiling point (PMCC-est.)  Extinguishing Media		N.D.		1 7 1	EL N.D.
Not usually necessary as the	nis produc	t does no	t readily s	upport comb	oustion.
Jse carbon dioxide, dry cher	mical,foam	or water	spray if ne	cessary.	
Special Fire Fighting Procedures Use waterspray to keep cont	tainers co	ol and va	pors down.	Do not allo	ow runof
to enter sewers or public v	watercours	es. Wear	SCBA in cher	mical fires	5.
Jnusual Fire and Explosion Hazards		· ·	,		
Aerosol container (pressuria	zed) may bu	rst if he	ated over 1	20°F.	