

# MATERIAL SAFETY DATA SHEET

7 / 7 / 1 / 1 / 22 1-30//- - 123 / 34 92651 EMERGENT TELER-

PRODUCTS CORPORATION

THE OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200 REQUIRES THAT THE INFORMATION CONTAINED ON THIS SHEET BE MADE AVAILABLE TO YOUR WORKERS.

INSTRUCT YOUR WORKERS TO HANDLE THIS PRODUCT PROPERLY

NAME:

ARMOR ALL AUTOMOTIVE LIQUID WAX

TYPE:

LIQUID

APPLICATION: AUTOMOTIVE WAX

23-JUL-90

#### SIGNAL WORD

THIS MATERIAL IS A "HEALTH HAZARD" AND/OR A "PHYSICAL HAZARD" AS DETERMINED WHEN REVIEWED ACCORDING TO THE REQUIREMENTS OF THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION 29 CFR PART 1910.1200 "HAZARD COMMUNICATION" STANDARD.

#### HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

MINERAL SPIRITS

ACGIH TLV: 100 MG/M3 OSHA PEL: 350 PPM NIOSH: 350 MG/M3 STODDARD SOLVENT ACGIH TLV: 100 MG/M3

OSHA PEL: 500 PPM

#### PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT SPECIFIC GRAVITY (H20 = 1) VAPOR PRESSURE (MM HG.)

40 DEC 5 40 DEC 6

194 DEG. F-(90 DEG. C)

MELTING POINT VAPOR DENSITY (AIR = 1)

-40 DEG. F—-40 DEG. C

EVAPORATION RATE (BUTYL ACETATE = 1)

<1 INSOLUBLE

.99

SOLUBILITY IN WATER PPEARANCE AND ODOR

GREY VISCOUS LIQUID.
PETROLEUM DISTILATE ODOR

#### FIRE AND EXPLOSION NAZARD DATA

FLASH POINT (METHOD USED) 150 DEG. F (TAG OPEN CUP) FLAMMABLE LIMITS - NOT DETERMINED

LEL: N.D. UEL: N.D.

EXTINGUISHING MEDIA - REGULAR FOAM OR CARBON DIOXIDE SPECIAL FIRE FIGHTING PROCEDURES: WEAR SELF CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE.

UNUSUAL FIRE AND EXPLOSION HAZARDS: VAPORS ARE HEAVIER THAN AIR. MAY TRAVEL ALONG GROUND. A RESIDUE CAN IGNITE BY HEAT OR PILOT FLAME.

# REACTIVITY DATA

NORMALLY STABLE

CONDITIONS TO AVOID: TEMPERATURE ABOVE 90 DEG. C MINERAL SPIRITS VOLATIZE OR ABOVE 150 DEG. F (TOC) IGNITE

INCOMPATIBILITY (MATERIALS TO AVOID) - N.A.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: METAL OXIDES, SILICON DIOXIDE, CARBON DIOXIDE AND TRACES OF INCOMPLETELY OXIDEIZED CARBON.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: NO CONDITION OTHER THAN EXCESSIVE HEAT.

#### HEALTH HAZARD DATA

INHALATION: AVOID PROLONGED OR REPEATED BREATING OF VAPOR. SKIN: AVOID PROLONGED OR REPEATED CONTACT WITH OPEN SORES. INGESTION: AVOID PROLONGED OR REPEATED CONTACT (ACUTE AND CHRONIC) CLASSIFIED AS MINIMALLY IRRITATING FOR WASHED EYES PER DRAIZE ARE IRRITANT TEST. REPEATED REPEATED CONTACT CAN CAUSE DERMATITIS.

LASSIFIED AS NON-TOXIC VIA DERMAL AND ORAL ROUTES PER ACUTE ORAL AND DERMAL TESTS.

INHALATION CAN CAUSE RESPIRATORY IRRITATION, NAUSEA.

HEADACHE IN CONFINED PLACES.

CARCINOGENICITY: N.D.

NTP - NO

IARC MONOGRAPHS: NONE

SIGNS AND SYMPTOMS OF OVER EXPOSURE: EYE IRRITATION.
BLURRED VISION, HEADACHES, DIZZINESS, WEAKNESS, FATIGUE,
NAUSEA, VOMITING AND DIARRHEA.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: PRE-EXISTING OCULAR. DERMAL OR RESPIRATORY CONDITIONS.

**EMERGENCY AND FIRST AID PROCEDURES** 

SKIN: WASH WITH PLENTY OF WATER FOR 15 MINUTES.
EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES.
INGESTION: IF SWALLOWED DO NOT INDUCE VOMITING. KEEP
SUBJECT WARM AND QUIETLY OBTAIN MEDICAL ATTENTION.
IF AFFECTED MOVE SUBJECT TO WELL VENTILATED AREA. IF
BREATHING IS DIFFICULT ADMINISTER OXYGEN.

#### PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED.
USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN FOR SALVAGE
AND/OR DISPOSAL

REMOVE ALL SOURCES OF IGNITION AND WEAR PROTECTIVE EQUIPMENT.

# WASTE DISPOSAL METHOD

IN ACCORDANCE WITH LOCAL STATE AND FEDERAL REGULATIONS THAT APPLY.

### STORAGE PRECAUTIONS

SKIN: AVOID OR MINIMIZE SKIN CONTACT. EYES: AVOID CONTAMINATING EYES.

INHALATION: DO NOT BREATHE VAPORS FOR PROLONGED PERIODS. REMOVE FROM SKIN AND FLUSH EYES WITH WATER AFTER CONTACT.

#### CONTROL MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE) NOT REQUIRED FOR GENERAL USE.

VENTILATION: USE LOCAL EXHAUST

SPECIAL / MECHANICAL (GENERAL) - NONE

WEAR RUBBER GLOVES AS RECOMMENDED TO PREVENT SKIN CONTACT.

EYE PROTECTION: NOT REQUIRED

WASH HANDS WITH SOAP AND WATER AFTER USING.

# DOT CLASSIFICATION

NOT REGULATED.

## DISCLAIMER

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING. THE ACCURACY OF ANY INFORMATION PROVIDED BY ARMOR ALL, except that the product shall conform to contracted specifications, and that the product does not infringe any valid. United States paten. The information provided herein was believed by Armor All to be accurate to the time of preparation. In proparen from sources believed to be reliable, but it is the respondible. The disease and procedures applicable to the safe handling and use of product and to determine the sulface. In the product for its intended use. Buver's exclusive remedy shall be too dampter and no dia microance whether as to product delivered or for non-delivery of product, and whether based on contract, preach of warranty negligence or otherwise shall be greater in amount than the purchase price of the quantity of product in respect or which damages are claimed. In no event shall Seller be liable for inclidental chooseduential damages whether Buver's claim is based on contract, preach of warranty hedligence or otherwise whether Buver's claim is based on contract, preach of warranty hedligence or otherwise.