



Material Safety Data Sheet

Copyright, 2005, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: COMPUBLEND (TM) II RINSE FREE HEAVY DUTY STRIPPER CONCENTRATE
1:4

MANUFACTURER: 3M
DIVISION: Commercial Care Division

ADDRESS: 3M Center
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 08/31/2005
Supersedes Date: 10/23/2002

Document Group: 11-3778-5

Product Use:

Specific Use: Designed to remove sealer or floor finish without rinsing or neutralizing. Follow directions to properly prepare your floor for recoating. Do not use on wood floors. **MUST BE DILUTED FOLLOWING THE DILUTION DIRECTIONS.**

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
WATER	7732-18-5	60 - 90
2-BUTOXYETHANOL	111-76-2	10 - 30
ETHANOLAMINE	141-43-5	7 - 13
ALCOHOLS, C12-14, ETHOXYLATED PROPOXYLATED	68439-51-0	1 - 5
SODIUM OCTYLSULFONATE	5324-84-5	< 1

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Liquid

Odor, Color, Grade: Clear dark blue, lemon scent

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: May cause target organ effects.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

May be harmful if absorbed through skin.

May be absorbed through skin and cause target organ effects.

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be harmful if inhaled.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be harmful if swallowed.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Flash Point > 200 °F

OSHA Flammability Classification: Class IIIB Combustible Liquid

5.2 EXTINGUISHING MEDIA

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Non-flammable: ordinary combustible material.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with water. Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

For industrial or professional use only. Keep out of the reach of children. Avoid breathing of vapors, mists or spray. Avoid skin contact. Avoid eye contact. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

7.2 STORAGE

Store away from areas where product may come into contact with food or pharmaceuticals. Store under normal warehouse conditions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use in a well-ventilated area.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields, Indirect Vented Goggles.

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Butyl Rubber, Neoprene, Nitrile Rubber. The following protective clothing material(s) are recommended: Apron - Neoprene.

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
2-BUTOXYETHANOL	ACGIH	TWA	20 ppm	Table A3
2-BUTOXYETHANOL	OSHA	TWA, Vacated	25 ppm	Skin Notation*
2-BUTOXYETHANOL	OSHA	TWA	50 ppm	Skin Notation*; Table Z-1
ETHANOLAMINE	ACGIH	TWA	3 ppm	
ETHANOLAMINE	ACGIH	STEL	6 ppm	
ETHANOLAMINE	OSHA	TWA	3 ppm	Table Z-1A
ETHANOLAMINE	OSHA	STEL	6 ppm	Table Z-1A
POLYETHYLENE GLYCOLS	AIHA	TWA, as aerosol	10 mg/m3	

* Substance(s) refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

VAC Vacated PEL: Vacated Permissible Exposure Limits [PEL] are enforced as the OSHA PEL in some states. Check with your local regulatory agency.

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Liquid
Odor, Color, Grade:	Clear dark blue, lemon scent
General Physical Form:	Liquid
Flash Point	> 200 °F

Boiling point	Approximately 212 °F
Specific Gravity	Approximately 1 [Ref Std: WATER=1]
pH	Approximately 12
Solubility in Water	Complete
Volatile Organic Compounds	15 - 40 % [Test Method: calculated per CARB title 2]
VOC Less H2O & Exempt Solvents	700 - 1300 g/l [Test Method: calculated per CARB title 2]
Viscosity	Approximately 100 centipoise

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion
Oxides of Sulfur	During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

A 3M Product Environmental Data Sheet (PED) is available.

CHEMICAL FATE INFORMATION

A 3M Product Environmental Data Sheet (PED) is available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
2-BUTOXYETHANOL (GLYCOL ETHERS)	111-76-2	10 - 30

STATE REGULATIONS

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

The components of this product are listed on the Australian Inventory of Chemical Substances.

All the components of this product are listed on China's Inventory of Chemical Substances.

The components of this product are in compliance with notification requirements in the Philippines.

The components of this product are listed on the Canadian Domestic Substances List.

INTERNATIONAL REGULATIONS

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 Flammability: 1 Reactivity: 0 Special Hazards: None

Acid/Base: Alkaline

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 Flammability: 1 Reactivity: 0 Protection: X - See PPE section.

Hazardous Material Identification System (HMIS®) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint and Coatings Association (NPCA).

Revision Changes:

Section 1: Product name was modified.
Section 1: Product use information was modified.
Section 16: NFPA hazard classification heading was modified.
Section 16: HMIS hazard classification heading was modified.
Section 3: Other potential health effects heading was modified.
Copyright was modified.
Section 8: Exposure guidelines data source legend was modified.
Section 4: First aid for eye contact - decontamination - was modified.
Section 4: First aid for eye contact - medical assistance - was modified.
Section 3: Potential effects from eye contact was modified.
Section 3: Potential effects from skin contact information was modified.
Section 3: Potential effects from inhalation information was modified.
Section 3: Potential effects from ingestion information was modified.
Section 5: Fire fighting procedures information was modified.
Section 6: Release measures information was modified.
Section 7: Handling information was modified.
Section 7: Storage information was modified.
Section 8: Eye/face protection phrase was modified.
Section 13: Waste disposal method information was modified.
Section 8: Eye/face protection information was modified.
Section 15: 311/312 hazard categories heading was modified.
Section 4: First aid for skin contact - medical assistance - was modified.
Section 4: First aid for inhalation - termination of exposure - was modified.
Section 4: First aid for inhalation - medical assistance - was modified.
Section 4: First aid for ingestion (swallowing) - medical assistance - was modified.
Section 10: Hazardous polymerization heading was modified.
Section 2: Ingredient table was modified.
Section 3: Other health effects information was modified.
Section 16: HMIS explanation was modified.
Section 16: NFPA explanation was modified.
Page Heading: Product name was modified.
Section 15: Inventories information was modified.
Section 15: EPCRA 313 text was modified.
Section 12: Ecotoxicological information heading was modified.
Section 12: Chemical fate information heading was modified.
Section 8: Exposure guidelines ingredient information was modified.
Section 8: Exposure guidelines legend was modified.
Section 8: Exposure guideline note was modified.
Section 5: Flash point information was modified.
Section 9: Property description for optional properties was modified.
Section 9: pH information was modified.

Section 16: NFPA hazard classification for special hazards was modified.
Section 9: Flash point information was modified.
Section 8: Respiratory protection - recommended respirators information was added.
Section 8: Skin protection - protective clothing recommendations was added.
Section 8: Respiratory protection - recommended respirators was added.
Section 8: Skin protection - protective clothing information was added.
Section 3: Immediate other hazard(s) was added.
Sections 3 and 9: Specific physical form information was added.
Sections 3 and 9: Specific physical form heading was added.
Section 8: Respiratory protection - recommended respirators guide was added.
Section 2: Ingredient phrase was added.
Section 8: Respiratory protection - recommended respirators punctuation was added.
Section 8: Skin protection - protective clothing - punctuation was added.
Section 12: Ecotoxicological phrase was added.
Section 12: Chemical Fate phrase was added.
Section 3: Immediate skin hazard(s) was deleted.
Section 3: Immediate eye hazard(s) was deleted.
Section 9: Density information was deleted.
Section 9: Vapor density value was deleted.
Section 9: Vapor pressure value was deleted.
Section 5: Flammable limits (UE) information was deleted.
Section 5: Flammable limits (LEL) information was deleted.
Section 5: Autoignition temperature information was deleted.
Section 9: Melting point information was deleted.
Section 9: Flammable limits (LEL) information was deleted.
Section 9: Flammable limits (UEL) information was deleted.
Section 9: Autoignition temperature information was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com