# APC+ **HEAVY DUTY UTILITY CLEANER**

HMIS RATING	
Health	2
Flammability	2
Reactivity	0

**MATERIAL** SAFETY DATA SHEET

NFPA 704 RA	TING
Health	2
Flammability	2
Reactivity	0
NFPA 30B LEVEL	
1	***************************************

KIMBALL-MIDWEST P.O. BOX 2470

COLUMBUS, OH 43216-2470 CORPORATE TELEPHONE: 614-219-6100 EMERGENCY TELEPHONE: 800-424-9300

|--|

	ICT IDENTIFICATION	
PART NUMBER	80-1552	
PRODUCT NAME	APC+ Heavy Duty Utility Cleaner	
CHEMICAL FAMILY		
DOT SHIPPING	Consumer Commodity ORM-D	
2. HAZARDOUS INGREDIENTS		

	HIVOIL		,
SPECIFIC CHEMICAL IDENTITY, COMMON NAMES	OSHA PEL	ACGIH TLV	REL %
*2 Butoxyethanol (111-76-2)	25ppm	25ppm	1-10
Tetrasodium salt of		• • •	
Ethylenediaminetetraacetic Acid (64-02-8)	NE	NE	1-10
N-alkyl-N, N-dimethyl-N-			
benzylammonium chloride (68391-01-5)	NE	NE	0.1-1.0
N-alkyl-N,N-dimethyl-N-			0
ethylbenzlyammonium (68956-79-6)	NE	NE	0.1-1.0
iquefied Petroleum Gas Mixture (68476-86-8)			
Propane (74-98-69)	1000ppm	1000ppm	(48-55)
n-Butane (106-97-8)	1000ppm	1000ppm	(45-49)
All chemical compounds marked with an asterisk (*) are toxic			ing of Section 313 of Title

III of the Superlund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. You must notify each person to whom this mixture of trade name product is sold. This statement must not be detached. Any copy or redistribution of this Material Safety Data Sheet shall include this statement. \*\*Ceiling

### 3. PHYSICAL DATA

## 4. FIRE AND EXPLOSION DATA

FLASH POINT	.>220°F
UPPER EXPLOSIVE LIMIT (%)	
LOWER EXPLOSIVE LIMIT (%)	
EXTINGUISHING MEDIA CO2, Foam, Dry Ch	
CDECIAL EIDEFICHTING DOCCEDUDES	

SPECIAL FIREFIGHTING PROCEDURES.............. Watermaybe used to cool containers to prevent pressure build up and explosion when exposed to extreme heat. Wear goggles and self-contained breathing apparatus.

FIRE AND EXPLOSION HAZARDS.....Fire fighters and others who may be exposed to the products of combustion should be equipped with NIOSH- approved positive pressure self-contained breathing apparatus and full protection clothing. At elevated temperature (over 54-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container source.

and stomach. May cause nausea, vomiting, pain and

#### 5 HEALTH EFFECTS DATA

э. пс	ALIN EFFECTS DATA
SHORT	TERM EFFECTS OF EXPOSURE
ROUTE OF ENTRY	. Eye, skin contact, inhalation
(ACUTE AND CHRONIC)	May affect the liver, kidneys, nervous system, lungs and/or respiratory system, heart or circulatory system, blood or blood forming organs, mucous membranes.
INHALATION	High concentration of prolonged exposure can be irritating to eye, nose, and respiratory tract High concentration may cause dizziness, drowsiness, headaches, incoordination, anesthetic or narcotic effects and other types of Central Nervous System Depression.
SKIN	Prolonged or repeated contact may cause irritation.
EYES	May cause moderate irritation.
INGESTION	Exposure by ingestion is unlikely since an aerosol since an aerosol, but if occurs, Irritation to the mouth throat

stomach upset.

#### 5. HEALTH EFFECTS DATA CON'T

MEDICAL CONDITIONS GENERALLY
AGGRAVATED BY EXPOSURE May aggravate preexisting eye, skin, respiratory, kidney, blood conditions.

	-
	FIRST AID PROCEDURES
EYE CONTACT	Flush with warm water for several minutes. Obtain medical attention.
SKIN CONTACT	. Wash affected area with soap and water. Obtain medical attention if irritation persists.
INGESTION	control center. Rinse mouth out with water and give another cupful to drink. Never give anything by mouth to an unconscious person.
INHALATION	Remove to fresh air. Apply artificial respiration if breathing has stopped. If symptoms develop or persist, seek medical attention.

SPECIAL HEALTH EFFECTS-CARCINOGEN (OSHA Guidelines) None Listed

6. REACTIVITY	
STABILITY	. Stable
*INCOMPATIBILITIES	Strong oxidizers, heat and open flame.
HAZARDOUS DECOMPOSITION	
PRODUCTS	Carbon monoxide, carbon dioxide and additional toxic chemicals may be formed in small amounts.
HAZARDOUS POLYMERIZATION	Will not occur under normal conditions.
HAZARDOUS POLYMERIZATION CONDITIONSNone known.	

7. PRECAUTIONS FOR SAFE HANDLING & USE
PROTECTIVE EQUIPMENT REQUIREMENTSTightly sealed goggles and protective rubber, polyethylene or neoprene gloves. Local exhaust ventilation may be necessary to control air contaminants to within TLVs during the use of this product.
WASH REQUIREMENTS Wash with soap and water.
SPILL OR LEAK PROCEDURES Avoid breathing vapors. Ventilate areas. Remove all sources of ignition. Clean up area with absorbent material and place in closed containers for disposal.
WASTE DISPOSAL METHODS Dispose of in accordance with local, state, and federal regulations.
HANDLING & STORAGEDo not allow can to exceed 120°F. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.
OTHER PRECAUTIONS Small pressurized containers of flammable products may be stored in areas suitable for ordinary combustible with respect to construction, drainage, control of ignition sources and ventilation except that they should not be stored in basements.

## 8. ADDITIONAL INFORMATION

Use self-contained breathing apparatus if TLV limits are exceeded. Do not eat or smoke while using. Wash hands after use. Use positive pressure air supplied respirator if there is potential for uncontrolled release, if exposure levels are unknown, or in any circumstance where air purifying respirators may not provide adequate protection.

THE INFORMATION GIVEN AND THE RECOMMENDATIONS MADE HEREIN APPLY TO OUR PRODUCT(S) ALONE AND ARE NOT COMBINED WITH OTHER PRODUCTS. SUCH INFORMATION IS BASED UPON OUR RESEARCH AND ON DATA FROM OTHER RELIABLE SOURCES AND IS BELIEVED TO BE ACCURATE. NO GUARANTEE OF ACCURACY IS MADE. IT IS THE PURCHASER'S RESPONSIBILITY BEFORE USING ANY PRODUCT TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS AND TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PURPOSES.



Specializing in Materials Management since 1923