72-62-7025-11

Material Safety Data Sheet



VALVOLINE OIL COMPANY
DIVISION OF ASHLAND OIL, INC.
P.O. BOX 391
ASHLAND, KENTUCKY 41114
(606) 329-3333

24-HOUR EMERGENCY TELEPHONE (606) 324-1133

000103

# CARQUEST 10W30

Page: 1

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (THE HAZARD COMMUNICATION STANDARD)

Product Name: CARQUEST 10W30

GENERAL PARTS, INC. P.O. BOX 25006 RALEIGH, NC 27611 ATTN: CHARLES P. SHAM 08 89 050 8155119-128

PRODUCT: CG530; INVOICE: REGST INVOICE DATE: 05/08/89 TO: Oata Sheet No: 0170829-007 Prepared: 10/17/88 Supersedes: 09/17/88

ARRAMATICANA ARRA

General or Generic ID: PETROLEUM BASED-LUBRICATING OIL

DOT Hazard Classification: NOT APPLICABLE

IF PRESENT, IARC, NTP AND OSHA CARCINOGENS AND CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III SECTION 313 ARE IDENTIFIED IN THIS SECTION.

SEE DEFINITION PAGE FOR CLARIFICATION

INGREDIENT % (by WT) PEL TLV Note SECTION STREETS WORK WISE WINES **Boiling Point** for COMPONENTI 40-55%) 425.00 Dec 218.33 Dec 760.00 mm Deg F Deg C) Hg Vapor Pressure NOT APPLICABLE Specific Vapor Density HEAVIER THAN AIR Specific Gravity .879 60.00 Deg F 15.55 Deg C) Percent Volatiles NOT APPLICABLE Evaporation Rate SLOWER THAN ETHER Appearance NOT SPECIFIED

LIQUID
Form
HOMOG SOLM
FORMSEN SECTION SUNCESURE SANDERS STEIN SUNFICION SECTION SECTI

FLASH POINT

State

> 400.0 Deg F

( 204.4 Deg C)

EXPLOSIVE LIMIT

IT UNAVAILABLE

EXTINGUISHING MEDIA: REGULAR FOAM OR CARBON DIOXIDE OR DRY CHEMICAL

HAZARDOUS DECOMPOSITION PRODUCTS: MAY FORM TOXIC MATERIALS:, CARBON DIOXIDE AND CARBON MONOXIDE, VARIOUS HYDROCARBONS, ETC.

FIREFIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WHEN FIGHTING FIRES.

WATER OR FOAM MAY CAUSE FROTHING WHICH CAN BE VIOLENT AND POSSIBLY ENDANGER THE LIFE OF THE FIREFIGHTER, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT, BURNING LIQUID.

SPECIAL FIRE & EXPLOSION HAZARDS: NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

NFPA CODES:

HEALTH- 1

FLAMMABILITY- 1

REACTIVITY- 0

DEBMISSIBLE EXPOSURE LEVEL A NOT ESTABLISHED ASSOCIATION OF THE PROPERTY OF TH

PERMISSIBLE EXPOSURE LEVEL: NOT ESTABLISHED FOR PRODUCT. SEE SECTION II.

EFFECTS OF ACUTE OVEREXPOSURE: FOR COMPONENT

TOXICOLOGICAL TESTING INDICATES THAT SIMILIAR PRODUCTS ARE NOT HAZARDOUS AS DEFINED BY OSHA (29 CFR 1910.1200). FIRST AID:

- IF ON SKIN: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE.
- IF IN EYES: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION.
- IF SWALLOWED: DO NOT INDUCE VOMITING, KEEP PERSON WARM AND QUIET, AND GET MEDICAL ATTENTION.
- IF BREATHED: IF AFFECTED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

72-62-7925-11

## MATERIAL SAFETY DATA SHEET



ASECTION WERE ACTION WITH THE PROPERTY OF THE

VALVOLINE OIL COMPANY DIVISION OF ASHLAND CIL, INC. P.O. BOX 391 ASHLAND, KENTUCKY 41114 (606) 329-3333

24-HOUR EMERGENCY **CELEPHONE** (635) \$24-1133

000103

# CARQUEST 10W30

Page:

HAZARDOUS FOLYMERIZATION: CANNOT OCCUR

STABILITY: STABLE

INCOMPATIBILITY: AVOID CONTACT WITH:, STRONG OXIDIZING AGENTS.

AND AND THE PROPERTY OF THE PR

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

SMALL SPILL: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND TRANSFER TO

SPILL: PREVENT RUN-OFF TO SEWERS, STREAMS OR OTHER BODIES OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES AS REQUIRED, THAT A SPILL HAS OCCURED. LARGE SPILL:

PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN COMPLETED. STOP SPILL AT SOURCE, DIKE AREA OF SPILL TO PREVENT SPREADING, PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID MAY BE TAKEN UP ON SAND, CLAY, EARTH, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS.

#### MASTE DISPOSAL METHOD:

SMALL SPILL: ALLOW VOLATILE PORTION TO EVAPORATE IN HOOD. ALLOW SUFFICIENT TIME FOR VAPORS TO COMPLETELY CLEAR HOOD DUCT WORK. DISPOSE OF REMAINING MATERIAL IN ACCORDANCE WITH APPLICABLE REGULATIONS.

LARGE SPILL: DESTROY BY LIQUID INCINERATION.

CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL

SECUREON SANDER SECURE CONTRACTOR SECURE SEC

RESPIRATORY PROTECTION: NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.

VENTILATION: NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.

PROTECTIVE GLOVES: NOT NORMALLY REQUIRED.

EYE PROTECTION: NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.

OTHER PROTECTIVE EQUIPMENT: NORMAL WORK CLOTHING COVERING ARMS AND LEGS.

A SECOND OF THE RECORD OF THE PROPERTY OF THE CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS GIVEN IN THIS DATASHEET MUST BE OBSERVED.

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

MANAGE AND REPORT OF THE PROPERTY OF THE PROPE

TOXICOLOGICAL TESTING INDICATES THAT SIMILAR PRODUCTS ARE NOT HAZARDOUS AS DEFINED BY OSHA 29 CFR 1910.1200 OR FHSA 16 CFR 1500.

### HANDLING & STORAGE:

DO NOT TRANSFER TO UNLABELED CONTAINER. DO NOT USE CUTTING OR WELDING TORCH ON THIS CONTAINER (EVEN EMPTY). FOR INDUSTRIAL USE ONLY. REFER TO MATERIAL SAFETY DATA SHEET (AVAILABLE UPON REQUEST) FOR FURTHER INFORMATION. 24-HOUR EMERGENCY NUMBER 1-800-ASHLAND

# FIRST AID:

EYES: FLUSH THOROUGHLY WITH WATER. CALL A PHYSICIAN IMMEDIATELY.

SKIN: WASH THOROUGHLY WITH SOAP AND WATER.

INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.