501 561 4443; # 2 6613891# 9K

"" " I CAMICA

FEWIX FRICTION "Squeal Repellent"

MATERIAL SAFETY DATA SHEET

THE OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200 REQUIRES THAT POSTOR ON THE STATE OF THE STAT

FOR INDUSTRIAL USE ONLY

PRODUCT NAME

base resix type : hodified ethylehe vinyl acetate copolyker

SIGNAL WORD

THIS MATERIAL IS NOT A " HEALTH HAZARD " OR A " PHYSICAL HAZARD " AS DETERMINED WHEN REVIEWED ACCORDING TO THE REQUIREMENTS OF THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION 29 CFR PART 1910.1200 " HAZARD COMMUNICATION " STANDARD.

CHEMICAL HAZARD RATING (HMIS)

HEALTH **= 0**

FIRE

REACTIVITY = 0

29 CFR1910.1200 HAZARDOUS INGREDIENTS/REPORTED HEALTH EFFECTS

CAS REGISTRY NO. TLV

MATERIAL DESCRIPTION

NOME KNOWN TO ADHESION SYSTEMS

2

PHYSICAL DATA

PERCENT VOLATILE :

APPEARANCE

ODOR

42

RED MILD

ACUTE HEALTH HAZARD DATA

SKIN ABSORPTION

INCESTION

INUALATION

INO HAZARDS KNOWN TO ADHESION SYSTEMS :NO HAZARDS KNOWN TO ADHESION SYSTEMS

EMBTEYE MOIESIAN OF ADHESION SYSTEMS

SKIN CONTACT

EYES

: NO HAZARDS KNOWN TO ADHESION SYSTEMS INO HAZARDS KNOWN TO ADHESION SYSTEMS

03/16/87 P 1

All recommendations and statements made, if any, are based on our research and experience. However, we cannot guarantee the results obtained through the use of our products, and all products are sold and samples given without any warranty, express or implied, of merchantability or of fitness for any particular purpose, or otherwise, and Jpon condition that the buyer shall determine the suitability of the products for his purpose. Buyer assumes the responsibility for all risks and liabilities which may result from the possession or use of our products. No representative of ours may change or waive any of the foregoing.

FENWIX FRICTION SQUEEL REPELLENT PRODUCT NAME BASE RESIN TYPE : HODIFIED ETHYLENE VINYL ACETATE COPOLYHER HANDLING PRECAUTIONS INHALATION: AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. SKIN : AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. EYES : AVOID PROLONGED OR REPEATED CONTACT WITH EYES. WASH THOROUGHLY AFTER HANDLING. IMERGENCY FIRST AID PROCEDURES ; REMOVE TO FRESH AIR. INHALATION : IN CASE OF IRRITATION, FLUSH WITH WATER. SKIN CONTACT : IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST EYE CONTACT 15 MINUTES. EYELIDS SHOULD BE HELD APART DURING IRRIGATION TO INSURE WATER CONTACT WITH FNTIRE SURFACE OF EYES AND LIDS. IF IRRITATION PERSISTS CALL A PHYSICIAN. FIRE AND EXPLOSION HAZARD DATA WILL NOT BURN UNLESS WATER EVAPORATED. IN CASE OF FIRE. USE WATER SPRAY, DRY CHEMICAL, FOAM, OR CO2. USE WATER TO COOL FIRE-EXPOSED CONTAINERS. REACTIVITY DATA NORHALLY STABLE AS DEFINED IN NEPA 704-12(4-3.1). MAJOR DECOMPOSITION PRODUCTS CO.CO2 PECIAL PROTECTION INFORMATION PROVED RESPIRATORY PROTECTION REQUIRED IN ABSENCE OF PROPER ENVIRON-_ntal control. Wearing safety glasses, safety, shoes, hard hats and SUITABLE CLOTHING IS STANDARD PRACTICE IN MANY INDUSTRIAL OPERATIONS. SPILL OR LEAK PROCEDURES LARGE QUANTITIES : ENCLOSE WITH DIKING MATERIAL TO PREVENT SEEPAGE INTO NATURAL BODIES OF WATER, THEN CONSULT ADHESION SYSTEMS SHALL QUANTITIES : SOAK UP WITH ABSORBENT MATERIAL AND REMOVE TO A CHENICAL DISPOSAL AREA. RECOVER FREE LIQUID. ABSORB RESIDUE AND DISPOSE OF ACCORDING TO

JASTE DISPOSAL METHOD

LOCAL, STATE, AND FEDERAL REQUIREMENTS.

STORAGE PRECAUTIONS

KEEP FROM FREEZING.

D.O.T. CLASSIFICATION

NOT REGULATED.

03/16/87 P 2

All recommendations and statements made, if any, are based on our research and experience. However, we cannot guarantee the results obtained through the use of our products, and all products are sold and samples given without any warranty, express or implied, of merchantability or of fitness for any particular purpose, or otherwise, and upon condition that the buyer shall determine the suitability of the products for his purpose. Buyer assumes the responsibility for all risks and liabilities which may result from the possession or use of our products. No representative of ours may change or waive any of the foregoing.