Material Safety Data Sheet



Best Bet

1. Product and company identification

Product name : Best Bet

Supplier : Betco Corporation

1001 Brown Avenue Toledo, Ohio 43607 (800) 333-2156

Manufacturer : Betco Corporation

1001 Brown Avenue Toledo, Ohio 43607

Code : 077 MSDS# : 077

 Validation date
 : 3/20/2013.

 Print date
 : 3/20/2013.

In case of emergency : Chemtrec (800) 424-9300

Product type : Liquid.

2. Hazards identification

Emergency overview

Physical state : Liquid. [Viscous liquid.]

Color : White.
Odor : Minty.
Signal word : Warning

Hazard statements : CORROSIVE. MAY BE HARMFUL IF ABSORBED THROUGH SKIN OR IF

SWALLOWED. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN

DAMAGE, BASED ON ANIMAL DATA.

Precautionary measures: Do not handle until all safety precautions have been read and understood. Obtain

special instructions before use. Do not breathe vapor or mist. Do not ingest. Do not eat, drink or smoke when using this product. Avoid prolonged contact with eyes, skin and clothing. Use personal protective equipment as required. Wash thoroughly after

handling.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Routes of entry : Dermal contact. Eye contact. Ingestion.

Potential acute health effects

Inhalation ; No known significant effects or critical hazards.

Ingestion: Harmful if swallowed. May cause burns to mouth, throat and stomach.

Skin : Harmful in contact with skin.

Eyes : Severely corrosive to the eyes. Causes severe burns.

Potential chronic health effects

Chronic effects : Contains material that may cause target organ damage, based on animal data.

Carcinogenicity
 No known significant effects or critical hazards.
 Mutagenicity
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Developmental effects
 No known significant effects or critical hazards.
 Fertility effects
 No known significant effects or critical hazards.

Target organs : Contains material which may cause damage to the following organs: kidneys, lungs,

upper respiratory tract, eyes, testes.

Best Bet

2. Hazards identification

Medical conditions aggravated by overexposure

Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

3. Composition/information on ingredients

Name	CAS number	%
Quartz (SiO2)	14808-60-7	20 - 40
Alkyl(C9-11) alcohol, ethoxylated	68439-46-3	1 - 5
Benzenesulfonic acid, C10-16-alkyl derivs.	68584-22-5	1 - 5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eve contact Check for and remove any contact lenses. Immediately flush eyes with plenty of water

for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately. In case of contact with eyes, rinse immediately with plenty of

water.

Skin contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes

while removing contaminated clothing and shoes. Wash clothing before reuse. Clean

shoes thoroughly before reuse. Get medical attention immediately.

Inhalation Move exposed person to fresh air. If not breathing, if breathing is irregular or if

respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention

immediately.

Wash out mouth with water. Do not induce vomiting unless directed to do so by medical Ingestion

personnel. Never give anything by mouth to an unconscious person. Get medical

attention immediately.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

Notes to physician No specific treatment. Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product : In a fire or if heated, a pressure increase will occur and the container may burst.

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

None known.

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

training.

Hazardous thermal decomposition products Decomposition products may include the following materials:

carbon dioxide carbon monoxide metal oxide/oxides

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

3/20/2013. 077 2/9

6. Accidental release measures

Personal precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). The spilled material may be neutralized with sodium carbonate, sodium bicarbonate or sodium hydroxide. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

Handling

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from alkalis. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Separate from alkalis. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Ingredient	Exposure limits
Quartz (SiO2)	OSHA PEL Z3 (United States, 9/2005). Notes: 250/(%SiO2+5) TWA: 250 mppcf 8 hour(s). Form: Respirable OSHA PEL Z3 (United States, 9/2005). Notes: 10/(SiO2+2) TWA: 10 mg/m³ 8 hour(s). Form: Respirable OSHA PEL 1989 (United States, 3/1989). TWA: 0.1 mg/m³, (as quartz) 8 hour(s). Form: Respirable dust ACGIH TLV (United States, 2/2010).
	TWA: 0.025 mg/m³ 8 hour(s). Form: Respirable fraction NIOSH REL (United States, 6/2009). TWA: 0.05 mg/m³ 10 hour(s). Form: respirable dust OSHA PEL Z3 (United States, 9/2005). Notes: 30/(%SiO2+2) TWA: 30 mg/m³ 8 hour(s). Form: Total dust.

8. Exposure controls/personal protection

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. >8 hours (breakthrough time): butyl rubber

Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Recommended: safety glasses

Skin

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Personal protective equipment (Pictograms)



9. Physical and chemical properties

Physical state : Liquid. [Viscous liquid.]

Flash point : Closed cup: Not applicable. [Product does not sustain combustion.]

Color : White.
Odor : Minty.
pH : 1.15 to 2.15
Relative density : 1.24562

Dispersibility properties : Dispersible in the following materials: cold water and hot water.

Solubility : Partially soluble in the following materials: cold water and hot water.

10. Stability and reactivity

Chemical stability

: The product is stable.

Conditions to avoid

: No specific data.

Incompatible materials

: Attacks many metals producing extremely flammable hydrogen gas which can form

explosive mixtures with air.

Reactive or incompatible with the following materials:

alkalis

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Possibility of hazardous

: Under normal conditions of storage and use, hazardous reactions will not occur.

reactions

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Alkyl(C9-11) alcohol, ethoxylated	LD50 Dermal	Rabbit	>2 g/kg	-
Benzenesulfonic acid, C10-16-alkyl derivs.	LD50 Oral LD50 Dermal	Rat Rabbit	1378 mg/kg 2000 mg/kg	-
	LD50 Oral	Rat	775 mg/kg	-

Conclusion/Summary

: Not available.

Chronic toxicity

Conclusion/Summary

: Not available.

Irritation/Corrosion

: Not available.

Sensitizer

Conclusion/Summary

Conclusion/Summary

: Not available.

Carcinogenicity

Conclusion/Summary

: Not available.

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Quartz (SiO2)	A2	1	-	+	Proven.	-

Mutagenicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary

: Not available.

Reproductive toxicity

Conclusion/Summary: Not available.

12. Ecological information

Ecotoxicity

: No known significant effects or critical hazards.

Aquatic ecotoxicity

Best Bet

12. Ecological information

Alkyl(C9-11) alcohol, ethoxylated	Acute EC50 2686 ug/L Fresh water	Daphnia - Daphnia magna - Neonate - <24 hours	48 hours
Benzenesulfonic acid, C10-16-alkyl derivs.	Acute LC50 8500 ug/L Fresh water Acute EC50 5.65 mg/L Fresh water	Fish - Pimephales promelas Crustaceans - Ceriodaphnia dubia - Neonate - <24 hours	96 hours 48 hours

Conclusion/Summary
Persistence/degradability

: Not available.

Conclusion/Summary

: Not available.

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	3265	Corrosive liquid, acidic, organic, n.o.s. (Dodecylbenzene Sulfonic Acid)	8	III	CORROSAVE	Limited quantity Yes.
TDG Classification	3265	Corrosive liquid, acidic, organic, n.o.s. (Dodecylbenzene Sulfonic Acid)	8	III		Explosive Limit and Limited Quantity Index
Mexico Classification	3265	Corrosive liquid, acidic, organic, n.o.s. (Dodecylbenzene Sulfonic Acid)	8	III		-
ADR/RID Class	3265	Corrosive liquid, acidic, organic, n.o.s. (Dodecylbenzene Sulfonic Acid)	8	III		-
IMDG Class	3265	Corrosive liquid, acidic, organic, n.o.s. (Dodecylbenzene Sulfonic Acid)	8	III		-

PG*: Packing group

15. Regulatory information

HCS Classification : Irritating material

Target organ effects

Sulfonic Acid)

U.S. Federal regulations : TSCA 8(a) IUR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: Quartz (SiO2); Alkylbenzenesulfonic

acid (C10-C16)

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Quartz (SiO2): Immediate (acute) health hazard, Delayed (chronic) health hazard;

Alkylbenzenesulfonic acid (C10-C16)

Clean Water Act (CWA) 311: sulphuric acid

Clean Air Act Section

112(b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

: Not listed

DEA List II Chemicals

(Essential Chemicals)

: Not listed

State regulations

Massachusetts : The following components are listed: SILICA, CRYSTALLINE, QUARTZ

New York: None of the components are listed.

New Jersey : The following components are listed: SILICA, QUARTZ; QUARTZ (SiO2)

Pennsylvania : The following components are listed: QUARTZ (SIO2)

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Quartz (SiO2)	Yes.	No.	No.	No.
titanium dioxide	Yes.	No.	No.	No.
sulphuric acid	Yes.	No.	No.	No.

Canada inventory

: At least one component is not listed in DSL but all such components are listed in NDSL.

International regulations

15. Regulatory information

International lists

Australia inventory (AICS): Not determined.

China inventory (IECSC): All components are listed or exempted.

Japan inventory: Not determined.

Korea inventory: All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

Chemical Weapons

Convention List Schedule I

Chemicals

: Not listed

Chemical Weapons

Convention List Schedule

II Chemicals

: Not listed

Chemical Weapons Convention List Schedule

: Not listed

III Chemicals

16. Other information

Label requirements

CORROSIVE. MAY BE HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of printing : 3/20/2013. : 3/20/2013. Date of issue Date of previous issue : 3/7/2013.

Best Bet

16. Other information

Version : 3

Prepared by : Not available.

✓ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.