72-62-7825-11

MATERIAL SAFETY DATA SHEET



#### VALVOLINE, INC. Subsidiary of Ashland Oil, Inc. P.O. BOX 14000 LEXINGTON, KENTUCKY 40512 (606) 264-7000

24-hour Emergency Telephone 1 (800) 274-5263 or 1-800-ASHLAND

009115

### CARQUEST DEXRONII/MERCON

Page: 1

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (THE HAZARD COMMUNICATION STANDARD)

Product Name: DEXRONII/MERCON

CARQUEST DIST CENTER
CARQUEST DIST CENTER
DIV OF GENERAL PARTS INC
DIV OF GENERAL PARTS INC
PO BOX 26006
RALEIGH NC 2761 27611 08 70 000 0834915-000

Data Sheet No: 0200299-004 04/26/90 02/19/90 Prepared Supersedes:

PRODUCT: 35300012 INVOICE: 045161 INVOICE DATE: 03/27/90 2635 MILLBROOK ROAD

ATTN: PLANT MGR / SAFETY DIR.

SECTION IL PRODUCT FUDENTIUS CATEGORY

General or Generic ID: PETROLEUM BASED-LUBRICATING OIL

DOT Hazard Classification: NOT APPLICABLE

SECTION SINGLE COMEONENTISM.

THE COMPOSITION OF THIS PRODUCT IS BEING WITHHELD AS A TRADE SECRET.

IF PRESENT, IARC, NTP AND OSHA CARCINOGENS AND CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III SECTION 313 ARE IDENTIFIED IN THIS SECTION.

SEE DEFINITION PAGE FOR CLARIFICATION

INGREDIENT

% (by YOL)

PEL

TLV

<u>Note</u>

ALIPHATIC PETROLEUM DISTILLATES CAS #: 64742-65-0

5 MG/M3

5 MG/M3

(1)

Notes:

( 1) PEL/TLV IS FOR OIL MIST. ACGIH SHORT TERM EXPOSURE LIMIT (STEL) FOR OIL MIST IS 10 MG/CUM. THE PARTY OF THE P

Boiling Point	for PRODUCT	DATIA
	-	> 425.00 Deg F ( 218.33 Deg C) a 760.00 mm Hg
~Vapor Pressure	NOT APPLICABLE	3 700.00 mm ng
Specific Vapor Density	NOT APPLICABLE	
Specific Gravity		
		.873 9 60.00 Deg F ( 15.55 Deg C)
Percent Volatiles	NOT APPLICABLE	( 15.55 Ueg C)
Evaporation Rate		CI CUED THAN A
Appearance		SLOWER THAN ETHER
State		RED COLOR
Form		LUQUID
	· ·	HOMOG SOLN

SECTION SEVERIFIED AND SEXPLOSION SENER MATERIAL SECTION SERVICES SECTION SECTI

FLASH POINTICOC

365.0 Deg F

185.0 Deg C)

EXPLOSIVE LIMIT

UNAVAILABLE

EXTINGUISHING MEDIA: REGULAR FOAM OR CARBON DIOXIDE OR DRY CHEMICAL

HAZARDOUS DECOMPOSITION PRODUCTS: MAY FORM TOXIC MATERIALS:, CARBON DIOXIDE AND CARBON MONOXIDE, VARIOUS

FIREFIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WHEN FIGHTING FIRES.

WATER OR FOAM MAY CAUSE FROTHING WHICH CAN BE VIOLENT AND POSSIBLY ENDANGER THE LIFE OF THE FIREFIGHTER, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT, BURNING LIQUID.

AL FIRE & EXPLOSION HAZARDS: NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

NFPA CODES:

HEALTH- 1

FLAMMABILITY- 1

REACTIVITY- 0

SEGUIONWHEALTHAHAZARDZDATA PERMISSIBLE EXPOSURE LEVEL: NOT ESTABLISHED FOR PRODUCT. SEE SECTION II.

EFFECTS OF ACUTE OVEREXPOSURE: FOR COMPONENT

TOXICOLOGICAL TESTING INDICATES THAT SIMILIAR PRODUCTS ARE NOT HAZARDOUS AS DEFINED BY OSHA (29 CFR 1910.1200). FIRST AID:

IF ON SKIN: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE.

COPYRIGHT 1990

CONTINUED ON PAGE: 2

72-62-7825-11

MATERIAL SAFETY DATA SHEET



# VALVOLINE, INC. Subsidiary of Asniand Oil, Inc. P.O. BOX 14000 LEXINGTON, KENTUCKY 40512 (606) 264-7000

24-hour Emergency Telephone 1 (800) 274-5263 or 1-800-ASHLAND

009115

# DEXRONII/MERCON

Page: 2

SECTION AVEH BALTH SHAZARD ADATTA ACCOMPLINUE OF

IF IN EYES: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION.

IF SWALLOWED: DO NOT INDUCE VOMITING, KEEP PERSON WARM AND QUIET, AND GET MEDICAL ATTENTION.

IF BREATHED: IF AFFECTED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

# SECTION WITH PRACTICATION ADATIA

HAZARDOUS POLYMERIZATION: CANNOT OCCUR

STABILITY: STABLE

INCOMPATIBILITY: AVOID CONTACT WITH:, STRONG OXIDIZING AGENTS.

# ASECTION AVIOLS PROJECT AND RELIGIOUS PROGEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

SMALL SPILL: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL.

LARGE SPILL: PREVENT RUN-OFF TO SEMERS, STREAMS OR OTHER BODIES OF WATER. IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES AS REQUIRED, THAT A SPILL HAS OCCURED.

PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN COMPLETED. STOP SPILL AT SOURCE, DIKE AREA OF SPILL TO PREVENT SPREADING, PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID MAY BE TAKEN UP ON SAND, CLAY, EARTH, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS.

#### WASTE DISPOSAL METHOD:

SMALL SPILL: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

LARGE SPILL: DESTROY BY LIQUID INCINERATION.

DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

# SECTEON SVIDE PROTECTIVE SEQUIPMENT STO BEAUSED

RESPIRATORY PROTECTION: NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.

VENTILATION: NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.

ROTECTIVE GLOVES: NOT NORMALLY REQUIRED.

EYE PROTECTION: NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.

OTHER PROTECTIVE EQUIPMENT: NORMAL WORK CLOTHING COVERING ARMS AND LEGS.

# CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS GIVEN IN THIS DATASHEET MUST BE OBSERVED.

SECTION CIX SPECIFAL SPRECAUTIONS CORROTHER COMMENTS

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING MITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

#### SECTION XX LIABEL ZINFORMATION

TOXICOLOGICAL TESTING INDICATES THAT SIMILAR PRODUCTS ARE NOT HAZARDOUS AS DEFINED BY OSHA 29 CFR 1910.1200 OR FHSA 16 CFR 1500.

#### HANDLING & STORAGE:

DO NOT TRANSFER TO UNLABELED CONTAINER. DO NOT USE CUTTING OR WELDING TORCH ON THIS CONTAINER (EVEN EMPTY). FOR INDUSTRIAL USE ONLY REFER TO MATERIAL SAFETY DATA SHEET (AVAILABLE UPON REQUEST) FOR FURTHER INFORMATION. 24-HOUR EMERGENCY NUMBER 1-800-ASHLAND.

#### FIRST AID:

EYES: FLUSH THOROUGHLY WITH WATER. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN: WASH THOROUGHLY WITH SOAP AND WATER.

INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

#### CHRONIC INFORMATION:

CONTAINS: PETROLEUM OIL

\*\*\* COMPONENTS APPEAR IN SECTION II \*\*\*