Material Safety Data Sheet

XTRAX-IT ENGINE TUNE-UP TREATMENT

QUICK IDENTIFIER Common Name: (used on label and list)

May be used to comply with OSHA's Hazard Communication Standard, 29CFR 1910, 1200. Standard must be consulted for specific requirements.

K & W STOCK # 2215, 2228, 2205 and 2250

NFPA Rating H-1, F-2, R-0

SECTION 1 -					
Manufacturer's					
Name K & W PRODUCTS Address		Emergency Selephone No.	213-720-4	680	
5801 S. EASTERN AVENUE City, State, and ZIP CITY OF COMMERCE, CA 90040	O Is	Other nformation	213=720=4		
Signature of Person Responsible for Preparation (Optional)	<u> </u>	2-4-	1-20-85 (revised	5/12/88]
SECTION 2 - HAZARDOUS INGREDIENTS/ID	ENTITY				
Hazardous Component(s) (chemical & common name(s))	OSHA PEL	ACGIH TLV	Other Exposure Limits	જ (optional	CAS NO.
Lubricating Base Oil	5.	000 (6	il mist)	64742-	-65-0
		400			-63-0
Isopropyl Toluene	and the second s	200			-88-3
Diacetone Alcohol		50		123-	-42-2
Xylene		100		1330-	-20-7
SECTION 3 - PHYSICAL & CHEMICAL CHARAC	Specific	0.0	Vapor	77.0	
SECTION 3 - PHYSICAL & CHEMICAL CHARAGE Boiling Point 180° F Vapor		0.9	Vapor Pressure (m	nm Hg) 33.0	
Boiling Point 180°F Heavier than air Vapor Density (Air = 1)	Specific Gravity (H,O=1)			nm Hg) 33.0	
Boiling 180°F Vapor Heavier than air Vapor Density (Air = 1)	Specific Gravity (H,O=1)	0.9 N/A		nm Hg) 33.0	
Boiling Point 180°F Heavier than air Vapor Density (Air = 1) Solubility in Water Slightly Appearance and Odor Clear red liquid, solvent odor	Specific Gravity (H,O=1) Reactivity in Water Melting			nm Hg) 33.0	
Boiling Point 180°F Heavier than air Vapor Density (Air = 1) Solubility in Water Slightly Appearance Clear red liquid, solvent odor SECTION 4 - FIRE & EXPLOSION DATA	Specific Gravity (H,O=1) Reactivity in Water Melting	N/A		nm Hg) 33.0	
Boiling Point 180°F Heavier than air Vapor Density (Air = 1) Solubility in Water Slightly Appearance and Odor Clear red liquid, solvent odor SECTION 4 - FIRE & EXPLOSION DATA Flash 45°F.7°C. Method TCC Flamm in Air Capacition Extinguisher	Specific Gravity (H,O=1) Reactivity in Water Melting Point N/A able Limits by Volume LEL Lower	N/A 2.5	Pressure (m UEL Upper		
Boiling Point 180°F Heavier than air Vapor Density (Air = 1) Solubility in Water Slightly Appearance and Odor Clear red liquid, solvent odor SECTION 4 - FIRE & EXPLOSION DATA Flash 45°F.7°C. Method TCC Flamm in Air Capacition Extinguisher	Specific Gravity (H,O=1) Reactivity in Water Melting Point N/A Table Limits by Volume LEL by Volume The foam or car	N/A 2.5 Chon dio	UEL Upper xide or dry	y chemical	
Boiling Point 180°F Heavier than air Vapor Density (Air = 1) Solubility in Water Slightly Appearance and Odor Clear red liquid, solvent odor SECTION 4 - FIRE & EXPLOSION DATA Flash 45°F.7°C. Method TCC Flamm in Air Auto-Ignition Temperature N/A Extinguisher Media Regular Special Fire	Specific Gravity (H,O=1) Reactivity in Water Melting Point N/A mable Limits LEL % by Volume Lower r foam or car pparatus with	N/A 2.5 Shon dio	UEL Upper xide or dry	y chemical	
Boiling Point 180°F Heavier than air Vapor Density (Air = 1) Solubility in Water Slightly Appearance and Odor Clear red liquid, solvent odor SECTION 4 - FIRE & EXPLOSION DATA Flash 45°F7°C. Method TCC Flamm in Air Media Regular Auto-Ignition Temperature N/A Extinguisher Media Regular Special Fire Fighting Procedures Self contained breathing and Unusual Fire and Explosion Hazards Vapors are heavier than air moved by ventilation and ignited by proceeding the self-self-self-self-self-self-self-self-	Specific Gravity (H,O=1) Reactivity in Water Melting Point N/A Mable Limits LEL % by Volume Lower r foam or car pparatus with r and may tra ilot lights,	N/A 2.5 chon dio a full evel alo other f	UEL Upper xide or dry face piece	y chemical e. und or may	be
Boiling Point 180°F Heavier than air Vapor Density (Air = 1) Solubility in Water Slightly Appearance and Odor Clear red liquid, solvent odor SECTION 4 - FIRE & EXPLOSION DATA Flash 45°F7°C Method TCC Flamm in Air Auto-Ignition Temperature N/A Extinguisher Media Regular Special Fire Fighting Procedures Self contained breathing ap Unusual Fire and Explosion Hazards Vapors are heavier than air	Specific Gravity (H,O=1) Reactivity in Water Melting Point N/A Mable Limits LEL % by Volume Lower r foam or car pparatus with r and may tra ilot lights,	N/A 2.5 chon dio a full evel alo other f	UEL Upper xide or dry face piece	y chemical e. und or may	be

SECTION 5 - PHYSICAL HAZARDS (REACTIVITY DATA) Stability Unstable
Stable X to Avoid Incompatability Materials to Avoid Contact with strong oxidizing agents.
Materials to Avoid) Golfedet with Strong Oxidizing agones.
Hazardous Decomposition Products Carbon diexide and/or carbon monoxide, etc.
Hazardous May Occur □ Conditions Polymerization Will Not Occur 兌 to Avoid
SECTION 6 – HEALTH HAZARDS
1. Acute 2. Chronic
Signs and Symptoms of Exposure Nasal and respiratory irritation, redness in eyes, defatting.
Medical Conditions Generally Aggravated by Exposure Redness, dizziness, weakness, fatigue, nausea, vomiting, diarrhea,
headache. Chemical Listed as Carcinogen National Toxicology Yes I.A.R.C. Yes OSHA Yes OSHA Yes
or Potential Carcinogen Program No Monographs No No No No No No No No
Emergency and First Aid Procedures
ROUTES OF ENTRY Remove individual to fresh air. 2. Eyes Wash with large amount of water. Get medical attention. 3. Skin Thoroughly wash exposed area with soap and water. 4. Ingestion Do not induce vomiting. Get immediate medical attention.
SECTION 7 - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES
Precautions to be Taken in Handling and Storage Store in cool dry place and away from source of ignition.
Other Precautions Use and store this product with adequate ventilation. Avoid breathing of vapors and prevent repeated or prolonged skin contact. Keep away from children.
Steps to be Taken in Case Material is Released or Spilled Eliminate all sources of ignition and absorb liquid on floor
absorbant.
Waste Disposal Methods (Consult federal, state, and local regulations) Dispose in accordance with governmental regulations.
TOTAL OF STREET PROTECTION INFORMATION/CONTROL MEASURES
SECTION 8 – SPECIAL PROTECTION INFORMATION/CONTROL MEASURES Respiratory Protection Self contained broathing appropriate
(Specify Type) Self contained breathing apparatus Ventilation Local Mechanical Special Other
Exhaust Local (General)
Gloves Rubber or plastic gloves Protection Chemical splash goggles
Other Protective Clothing or Equipment Impermeable clothing
Work/Hygienic Practices Avoid breathing of vapors and skin contact.

IMPORTANT
Do not leave any blank spaces. If required information is unavailable, unknown, or does not apply, so indicate.