

**PRODUCTS CORPORATION**

THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) REQUIRES THAT THE INFORMATION CONTAINED ON THIS SHEET BE MADE AVAILABLE TO ALL EMPLOYEES.

INSTRUCT YOUR WORKERS TO HANDLE THIS PRODUCT PROPERLY.

NAME: NO. "7" AUTO POLISH 0111N (New # 01110)  
 PRODUCT TYPE: LIQUID POLISH  
 APPLICATION: AUTO FINISHES

30-Sep-88

**SIGNAL WORD CAUTION!**

THIS MATERIAL PRESENTS POSSIBLE HEALTH HAZARDS AS DETERMINED WHEN REVIEWED ACCORDING TO THE REQUIREMENTS OF THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION 29 CFR PART 1910.1200 "HAZARD COMMUNICATION" STANDARD.

**CHEMICAL HAZARD RATING**

HEALTH=1(SLIGHT)  
 FIRE=1(SLIGHT)  
 REACTIVITY=0(LEAST)  
 CHRONIC=\*

**SAFETY PRACTICES.**

THESE PRACTICES INCLUDE AVOIDING UNNECESSARY EXPOSURE AND REMOVAL OF THE MATERIAL FROM EYES, SKIN AND CLOTHING. WASH THOROUGHLY AFTER HANDLING.

**29CFR1910.1200 HAZARDOUS INGREDIENTS/REPORTED HEALTH EFFECTS**

CAS/REGISTRY NO. MATERIAL DESCRIPTION % RANGE

THE INGREDIENTS LISTED BELOW HAVE BEEN ASSOCIATED WITH ONE OR MORE OF THE LISTED IMMEDIATE AND OR DELAYED (\*) HEALTH HAZARDS. RISK OF DAMAGE AND EFFECTS DEPENDS UPON DURATION AND LEVEL OF EXPOSURE. BEFORE USING OR HANDLING, READ AND UNDERSTAND THE MSDS.

**7631-86-9 \*SILICON DIOXIDE 10-30**  
 CAN CAUSE LUNG FIBROSIS. PRE-EXISTING RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE.  
 —SEE FOOTNOTE C.  
 ACGIH TLV: DUST 20 MPPCF TWA  
 OSHA PEL: DUST 20 MPPCF (80 MG/M3) TWA  
 NIOSH DOCUMENT NUMBER: 75-120

**14808-60-7 \*QUARTZ 0.1-1**  
 SUSPECT CANCER HAZARD. MAY CAUSE CANCER. THIS MATERIAL HAS BEEN LISTED BY NTP, IARC OR OSHA AS A SUSPECTED HUMAN CARCINOGEN.  
 ACGIH TLV: RESPIRABLE DUST 0.1 MG/M3 TWA  
 OSHA PEL: SEE 29CFR1910.1000 TABLE Z-3

**64741-89-5 SOLVENT REFINED LIGHT PARAFFINIC DISTILLATE (PETROLEUM) 5-10**  
 —SEE FOOTNOTE C.  
 ACGIH TLV: OIL MIST 5 MG/M3 TWA  
 OSHA PEL: OIL MIST 5 MG/M3 TWA

FOOTNOTE C: AS OF THE DATE OF ISSUANCE OF THIS DOCUMENT, THIS MATERIAL HAS NOT BEEN LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN.

**PHYSICAL DATA**

ODOR: FRUITY  
 GALLON WEIGHT LB/GAL: 8.7 LBS.  
 GENERAL APPEARANCE: THICK BROWN LIQUID  
 PH: 6.5  
 FLASH POINT, TCC: 212F+

**ACUTE HEALTH HAZARD DATA**

SKIN ABSORPTION: NOT TOXIC DERMALLY WHEN TESTED AS DESCRIBED IN 16 CFR PART 1500.3 (c) (1) AND (2).  
 INGESTION: NOT TOXIC ORALLY WHEN TESTED AS DESCRIBED IN 16 CFR PART 1500.3 (c) (1) AND (2).  
 INHALATION: NOT TOXIC BY INHALATION WHEN TESTED AS DESCRIBED IN 16 CFR PART 1500.3 (c) (1) AND (2).  
 SKIN: MAY CAUSE IRRITATION ON PROLONGED OR REPEATED CONTACT. NOT A PRIMARY IRRITANT (PRIMARY SKIN IRRITATION INDEX LESS THAN 5.0/8.0) WHEN TESTED AS DESCRIBED IN 16 CFR PART 1500.41.  
 EYES: MAY CAUSE IRRITATION ON PROLONGED OR REPEATED CONTACT. SLIGHTLY IRRITATING WHEN TESTED AS DESCRIBED IN 16 CFR PART 1500.42.

**HANDLING PRECAUTIONS**

SKIN: PERSONS WITH SENSITIVE SKIN SHOULD AVOID PROLONGED, CONTINUOUS CONTACT WITH SKIN. IF IRRITATION DEVELOPS, DISCONTINUE USE.  
 EYES: AVOID PROLONGED OR REPEATED CONTACT WITH EYES.  
 HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND

**EMERGENCY AND FIRST AID PROCEDURES**

INGESTION: IF ACCIDENTLY SWALLOWED, DILUTE BY DRINKING LARGE QUANTITIES OF WATER. IMMEDIATELY CONTACT POISON CONTROL CENTER OR HOSPITAL EMERGENCY ROOM FOR ANY OTHER ADDITIONAL TREATMENT DIRECTIONS.  
 SKIN CONTACT: IN CASE OF IRRITATION, FLUSH WITH WATER.  
 EYE CONTACT: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER. CALL A PHYSICIAN IF IRRITATION PERSISTS.

**FIRE AND EXPLOSION HAZARD DATA**

WILL BURN  
 IN CASE OF FIRE, USE WATER SPRAY, DRY CHEMICAL, FOAM OR CO2. USE WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL.

**REACTIVITY DATA**

NORMALLY STABLE AS DEFINED IN NFPA 704-1214-3.1  
 HAZARDOUS POLYMERIZATION: WILL NOT OCCUR  
 INCOMPATIBILITIES: OXIDIZERS, ACIDS OR BASES.  
 DECOMPOSITION PRODUCTS MAY INCLUDE: OXIDES OF CARBON AND NITROGEN.

**CONTROL MEASURES**

NO SPECIAL CONTROL MEASURES NECESSARY UNDER NORMAL CONDITIONS OF USE

**PERSONAL PROTECTION INFORMATION**

NO SPECIAL PROTECTION NECESSARY

**SPILL OR LEAK PROCEDURES**

SOAK UP WITH ABSORBENT MATERIAL AND REMOVE TO A CHEMICAL DISPOSAL AREA.  
 PREVENT ENTRY INTO NATURAL BODIES OF WATER

**WASTE DISPOSAL**

RECOVER FREE LIQUID. ABSORB RESIDUE AND DISPOSE OF ACCORDING TO LOCAL, STATE, PROVINCIAL, AND FEDERAL REQUIREMENTS

**STORAGE PRECAUTIONS**

KEEP CONTAINER CLOSED.  
 STORE IN A COOL, DRY PLACE.

**DOT CLASSIFICATION**

NOT REGULATED

---

### DISCLAIMER

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY ARMOR ALL, except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States patent. The information provided herein was believed by Armor All to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of product and to determine the suitability for the product for its intended use. Buyer's exclusive remedy shall be for damages and cost and attorney's fees, whether as to product delivered or for non-delivery of product, and whether based on contract, breach of warranty, negligence or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. Seller shall be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.

---