

# MATERIAL SAFETY DATA SHEET

MSDS# BS05

ABBREVIATIONS: NA = NOT APPLICABLE  
ND = NOT DETERMINED  
NE = NOT ESTABLISHED

HEALTH = 1  
FLAMMABILITY = 0  
REACTIVITY = 0  
PERSONAL PROTECTION = B

## SECTION 1 - PRODUCT IDENTIFICATION

PRODUCT NAME: BRITE STRIPE WHITE

PRODUCT TYPE: LATEX PAINT

PIONEER MANUFACTURING COMPANY  
4529 INDUSTRIAL PARKWAY  
CLEVELAND, OHIO 44135  
TELEPHONE: 800-877-1500

EMERGENCY TELEPHONE (800) 535-5053  
INFOTRAC

DATE PREPARED: 1/5/04

PREPARED BY: GSS

D.O.T. SHIPPING NAME NOT REGULATED

## SECTION 2 - HAZARDOUS INGREDIENTS

CHEMICAL NAME:	CAS NO.	OSHA PEL	ACGIH TLV	% WT
MONOETHANOL AMINE	141-43-5	3 ppm	6 ppm	
ACRYLIC LATEX	N.A.	N.E.	N.E.	
WATER	7732-18-5	N.E.	N.E.	
CALCIUM CARBONATE	1317-65-3	5 mg/m <sup>3</sup> RESPIRIBLE DUST		
TITANIUM DIOXIDE	13463-67-7	5 mg/m <sup>3</sup> RESPIRIBLE DUST		

\* SUBJECT TO REPORTING REQUIREMENTS OF SARA TITLE III SECTION 313, 40 CFR 372

## SECTION 3 - PHYSICAL DATA

BOILING POINT (° F) 212  
VAPOR PRESSURE: EQUAL TO WATER  
VAPOR DENSITY: EQUAL TO WATER  
SOLUBILITY IN WATER: SOLUBLE  
APPEARANCE/ODOR: WHITE, VISCOUS LIQUID, MILD LATEX ODOR

SPECIFIC GRAVITY: 1.35  
MELTING POINT: N.A.  
EVAPORATION RATE (BUAC=1): EQUAL TO WATER  
pH: 9-10

## SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT (METHOD USED): NONE, SETAFLAMMABILITY LIMITS: LEL N.A. UEL N.A.

EXTINGUISHING MEDIA: WATER, FOAM, CARBON DIOXIDE, DRY CHEMICAL.

SPECIAL FIRE FIGHTING PROCEDURES: NONE

UNUSUAL FIRE FIGHTING AND EXPLOSION HAZARDS: CLOSED CONTAINERS MAY EXPLODE DUE TO STEAM FORMATION FROM EXPOSURE TO HIGH HEAT. USE WATER SPRAY TO COOL.

**FOR CHEMICAL EMERGENCY**

Call INFOTRAC

**1-800-535-5053****24 Hrs. per day, 7 days per week**

