



THE OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200 REQUIRES THAT THE INFORMATION CONTAINED ON THIS SHEET BE MADE AVAILABLE TO YOUR WORKERS.

INSTRUCT YOUR WORKERS TO HANDLE THIS PRODUCT PROPERLY

NAME: NO. "7" CARB & CHOKE SPRAY 3715N  
TYPE: AEROSOL  
APPLICATION: CARB & CHOKE CLEANER

37150

03-Dec-85

**SIGNAL WORD—DANGER!**

THIS MATERIAL IS A "HEALTH HAZARD" AND/OR A "PHYSICAL HAZARD" AS DETERMINED WHEN REVIEWED ACCORDING TO THE REQUIREMENTS OF THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION 29 CFR PART 1910.1200 "HAZARD COMMUNICATION" STANDARD.

**CHEMICAL HAZARD RATING**

HEALTH = 2(MODERATE)  
FIRE = 4(EXTREME)  
REACTIVITY = 0(LEAST)

**29CFR1910.1200 HAZARDOUS INGREDIENTS/REPORTED HEALTH EFFECTS CAS REGISTRY NO. MATERIAL DESCRIPTION**

**74-98-6 PROPANE**  
THIS MATERIAL IS A SIMPLE ASPHYXIANT. SIGNS AND SYMPTOMS OF OVEREXPOSURE INCLUDE CYANOSIS, RESPIRATORY DISTRESS, HEADACHE, DIZZINESS, DROWSINESS, UNCONSCIOUSNESS AND ASPHYXIATION.  
CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION.  
ACGIH EXPOSURE LIMIT: SEE ACGIH TLVS, APPENDIX E  
OSHA 29CFR1910 EXPOSURE LIMIT: 1000 PPM, 8-HR TWA

**123-42-2 DIACETONE ALCOHOL**  
OVEREXPOSURE MAY CAUSE LIVER AND/OR KIDNEY DAMAGE BASED ON TEST WITH LABORATORY ANIMALS.  
CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND EVEN ASPHYXIATION.  
ACGIH EXPOSURE LIMIT: 50 PPM, 8-HR TWA  
OSHA 29CFR1910 EXPOSURE LIMIT: 50 PPM, 8-HR TWA  
NIOSH DOCUMENT NUMBER: 78-173

**1330-20-7 XYLENE**  
OVEREXPOSURE MAY CAUSE LIVER AND/OR KIDNEY DAMAGE.  
CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND EVEN ASPHYXIATION.  
ACGIH EXPOSURE LIMIT: SKIN - 100 PPM, 8-HR TWA  
OSHA 29CFR1910 EXPOSURE LIMIT: 100 PPM, 8-HR TWA  
NIOSH DOCUMENT NUMBER: 75-168

**PHYSICAL DATA**

GENERAL APPEARANCE: CLEAR LIQUID  
ODOR: AROMATIC

**ACUTE HEALTH HAZARD DATA**

SKIN ABSORPTION: NO HAZARDS KNOWN TO BORDEN.  
INGESTION: MAY BE HARMFUL IF SWALLOWED.  
INHALATION: MAY BE HARMFUL IF INHALED. LIQUID OR VAPOR CAN CAUSE IRRITATION OF NOSE, THROAT AND LUNGS.  
SKIN: SLIGHTLY TO MODERATELY IRRITATING (PRIMARY SKIN IRRITATION INDEX LESS THAN 5.0/8.0) WHEN TESTED AS DESCRIBED IN 16 CFR PART 1500.41.  
EYES: SLIGHTLY IRRITATING WHEN TESTED AS DESCRIBED IN 16 CFR PART 1500.42.

**HANDLING PRECAUTIONS**

INHALATION: AVOID BREATHING VAPOR OR MIST.  
USE WITH ADEQUATE VENTILATION.  
SKIN: AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.  
EYES: AVOID PROLONGED OR REPEATED CONTACT WITH EYES. WASH THOROUGHLY AFTER HANDLING.

**EMERGENCY AND FIRST AID PROCEDURES**

INTERNAL: IF SWALLOWED, DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.  
INHALATION: REMOVE TO FRESH AIR.  
SKIN CONTACT: IN CASE OF IRRITATION, FLUSH WITH WATER.  
EYE CONTACT: FLUSH THOROUGHLY WITH WATER. IF IRRITATION PERSISTS, CALL A PHYSICIAN.

**FIRE AND EXPLOSION HAZARD DATA**

EXTREMELY FLAMMABLE.  
CONTENTS UNDER PRESSURE: EXPOSURE TO HIGH TEMPERATURE MAY CAUSE BURSTING. AVOID RADIATORS, STOVES, DIRECT SUNLIGHT, OR OTHER HEAT SOURCE.  
DO NOT PUNCTURE OR INCINERATE CONTAINER.  
DO NOT SPRAY NEAR OPEN FLAME.

**REACTIVITY DATA**

NORMALLY STABLE AS DEFINED IN NFPA 704-12(4-3.1).

**SPECIAL PROTECTION INFORMATION**

APPROVED RESPIRATORY PROTECTION REQUIRED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL.  
WEARING SAFETY GLASSES, SAFETY SHOES, HARD HATS AND SUITABLE CLOTHING IS STANDARD PRACTICE IN MANY INDUSTRIAL OPERATIONS.

**SPILL OR LEAK PROCEDURES**

SOAK UP WITH ABSORBENT MATERIAL AND REMOVE TO A CHEMICAL DISPOSAL AREA.  
PREVENT ENTRY INTO NATURAL BODIES OF WATER.

**WASTE DISPOSAL METHOD**

DISPOSE OF ACCORDING TO LOCAL, STATE, AND FEDERAL REQUIREMENTS.  
EMPTY CONTAINER: MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEARBY. INCINERATION WILL CAUSE CONTAINER TO BURST VIOLENTLY.

**STORAGE PRECAUTIONS**

KEEP CONTAINER CLOSED.  
STORE IN A COOL, DRY PLACE.

**DOT CLASSIFICATION**

ORM-D CONSUMER COMMODITY

DISCLAIMER—SEE REVERSE SIDE

### **DISCLAIMER**

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY BORDEN, except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States patent. The information provided herein was believed by Borden to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of product and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as to product delivered or for non-delivery of product, and whether based on contract, breach of warranty, negligence or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.